

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: WHEEL & TIRE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Car wheel cleaner

1.3. Details of the supplier of the safety data sheet

Company name: Fireball Co., Ltd.

27

Geuringongdan 4-gil

Yangsang-si, Gyeongsangnamdo

S.Korea

50540

S.Korea

Tel: 82-10-6462-8888

Email: kumsoli@hotmail.com

1.4. Emergency telephone number

Emergency tel: 2102491136(24H)

Section 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification under CLP: Eye Dam. 1: H318; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SAFETY DATA SHEET

WHEEL & TIRE

Page: 2

P310: Immediately call a POISON CENTER or doctor.

P321: Specific treatment (see supplemental first aid instruction on this label)

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POLYOXYETHYLENE ALKYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
617-534-0	84133-50-6	-	Eye Irrit. 2: H319	1-10%

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

200-573-9	64-02-8	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%
-----------	---------	---	--------------------------------------	-------

SODIUM TRI-OXYETHYLENE LAURY ETHER SULFATE

221-416-0	9004-82-4	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

POTASSIUM HYDROXIDE

215-181-3	1310-58-3	-	Acute Tox. 4: H302; Skin Corr. 1A: H314	1-10%
-----------	-----------	---	---	-------

Non-classified ingredients:

WATER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	7732-18-5	-	-	70-90%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

[cont...]

SAFETY DATA SHEET

WHEEL & TIRE

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

SAFETY DATA SHEET

WHEEL & TIRE

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

POTASSIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Flower Scent

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: No data available.

Boiling point/range°C: 100

Flammability limits %: lower: No data available.

Flash point°C: exact value...

Autoflammability°C: No data available.

Relative density: 0.990~1.080

VOC g/l: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

pH: >12

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

WHEEL & TIRE

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM TRI-OXYETHYLENE LAURY ETHER SULFATE

ORAL	RAT	LD50	5000	mg/kg
------	-----	------	------	-------

POTASSIUM HYDROXIDE

ORL	RAT	LD50	273	mg/kg
-----	-----	------	-----	-------

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET

WHEEL & TIRE

Page: 6

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM TRI-OXYETHYLENE LAURY ETHER SULFATE

Ceriodaphnia dubia	48H EC50	2.43-4.01	mg/l
--------------------	----------	-----------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(POLYOXYETHYLENE ALKYL ETHER; TETRASODIUM ETHYLENE DIAMINE
TETRAACETATE; SODIUM TRI-OXYETHYLENE LAURY ETHER SULFATE; POTASSIUM
HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

[cont...]

SAFETY DATA SHEET

WHEEL & TIRE

Page: 7

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.